

## PG23HP-P.160...D 2500 bar G1/2B lower mount

### "Bourdon Tube Pressure Gauge, Safety Pattern"

Numer wyrobu:	83123814	
Ilość:	1 szt.	
Kod zamówienia:	PG23HP-P4-D-5G-F-BG625Z-GD-UZHQCZZ-ZZZ IZZZZZZ11ZZZ	213D1I3W01-
Przeгляд:	PG23HP-P.160...D 2500 bar G1/2B lower mount class 1.0 Ingress protection: IP 65 Restrictor: stainless steel, D 0.6 with thread protection Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number on label	
Szczegóły:	"Bourdon Tube Pressure Gauge, Safety Pattern" High Pressure starting at 2000 bar, Heavy-Duty Model PG23HP-P Specifications according to data sheet: PM 02.29 Measuring system: NiFe-alloy combined with stainless steel Liquid Damping (case filling): without filling Nominal size: 160 mm Measuring range: gauge pressure range Scale range: 0...2500 bar Process connection: G 1/2 B Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: standard pointer Accuracy class: class 1.0 Ingress protection: IP 65 Permissible medium temperature: + 200 °C with thread protection Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* Serial number: Serial number on label	